



TECHNICAL DATA SHEET:

GENERAL DESCRIPTION:

YEAR OF CONSTRUCTION 2003
MAKE HRI
TYPE MECHANICAL
PRESSURE RATED 3 000 PSI

MAST:

MAKE AND TYPE HRI 250 - SINGLE
STATIC HOOK LOAD 80 METRIC TONS
HEIGHT 66 FT (20.12 M)

WORKING PLATFORM:

MAKE AND TYPE HRI - ADJUSTABLE
HEIGHT 1.5 FT TO 8.0 FT (0.5 M TO 2.5 M)
CLEAR HEIGHT 1.0 FT TO 7.5 FT (0.3 M TO 2.3 M)

DRAWWORKS:

MAKE AND TYPE HRI 250 - 38 X 10
POWER RATING 350 HP
DRILLING LINE 1"
AUXILIARY BRAKE DRIVE PARMAC 122 MECHANICAL

TOP DRIVE SYSTEM:

MAKE AND TYPE BOWEN - S 3.5
LOAD RATING 120 TONS
MAXIMUM TORQUE 8 000 FT.LBS
MAXIMUM SPEED 172 RPM
DRIVE HYDRAULIC

BOP STACK:

SIZE 7-1/16"
WORKING PRESSURE 3 000 PSI
MODEL ANNULAR PREVENTER
MANUFACTURING HYDRIL GK

RIG POWER SUPPLY:

DRAWWORKS ENGINE 1 X GM 6V92T
POWER RATING 350 HP
MUD PUMPS ENGINE 1 X CATERPILLAR 3406
POWER RATING 400 HP
GENERATOR 1 X LEROY SOMER
POWER RATING 110 KVA
TDS ENGINE 1 X DETROIT DIESEL 6V71
POWER RATING 230 HP

MUD PUMPS:

MAKE AND TYPE 1 X EMSCO F-350
POWER RATING 350 HP
DRIVE MECHANICAL

MUD SYSTEM:

MUD TANKS 43 M3 (270 BBLs)
HOPPERS 1