



TECHNICAL DATA SHEET:

GENERAL DESCRIPTION:

YEAR OF CONSTRUCTION 2005
 MAKE HRI
 TYPE MECHANICAL
 PRESSURE RATED 3 000 PSI

SUBSTRUCTURE:

MAKE AND TYPE HRI -TELESCOPIC
 HEIGHT 10.5 FT (3.2 M)
 CLEAR HEIGHT 9.84 FT (3.0 M)

MAST:

MAKE AND TYPE HRI 250 - SINGLE
 STATIC HOOK LOAD 80 METRIC TONS
 HEIGHT 66 FT (20.12 M)

DRAWWORKS:

MAKE AND TYPE HRI 250 - 38 X 10
 POWER RATING 350 HP
 DRILLING LINE 1"
 AUXILIARY BRAKE DRIVE PARMAC 122 MECHANICAL

TOP DRIVE SYSTEM:

MAKE AND TYPE BOWEN - S 3.5
 LOAD RATING 120 TONS
 MAXIMUM TORQUE 8 000 FT.LBS
 MAXIMUM SPEED 172 RPM
 DRIVE HYDRAULIC

BOP STACK:

SIZE 11"
 WORKING PRESSURE 5 000 PSI
 TYPE ANNULAR PREVENTER
 MODEL SHAFFER
 TYPE RAMS PREVENTER
 MODEL SHAFFER LWS (DOUBLE)

RIG POWER SUPPLY:

DRAWWORKS ENGINE 1 X GM 6V92T
 POWER RATING 350 HP
 MUD PUMPS ENGINES 2 X CATERPILLAR 3406
 POWER RATING 400 HP
 GENERATOR 1 X LEPRON
 POWER RATING 300 KVA
 TDS ENGINE 1 X DETROIT DIESEL 6V71
 POWER RATING 230 HP

MUD PUMPS:

MAKE AND TYPE 2 X HALLIBURTON HT400
 POWER RATING 2 X 400 HP
 DRIVE MECHANICAL

MUD SYSTEM:

MUD TANKS 60 M3 (380 BBLs)
 HOPPERS 1